

EARTH CONTACT RESISTANCE TESTER

MODEL : PE 900



- Designed with relevant ISI drafted specification.
- Measures earthing contact resistance of Domestic/Industrial Electrical Appliances.
- Housed in smart & compact MS cabinet.

TECHNICAL SPECIFICATIONS :

- Test Current : 3 to 30 A, continuously variable by means of dimmerstat monitored on

Digital Current Meter having

Display : 3.5 digit, 0.5"ht red LED.
Range : 0-30 0A
Resolution : 0.01 A
Accuracy : 0.6% \pm 1 count
Test Voltage : 0-6 V max.

Monitored on Digital Voltmeter having

Display : 3.5 digit, 0.5"ht red LED.
Range : 0-19.99V AC Resolution : 0.01 V
Accuracy : 0.6% \pm 1 count Power : 230 V AC \pm 10%, 50Hz.
Dimensions : 360(W) x 140(H) x 220(D) mm³

OPTIONS

1. direct display of earthing contact resistance.
2. Calibration certificate traceable to international standards meeting ISO 9000/ISI requirements.

PREMIER ELECTROSYSTEMS

3 & 204A, Planet Industrial Estate, Subhash Rd, Vile Parle (East), Mumbai : 400 057, INDIA

TEL : +91 22 2616 99 23 / +91 22 2616 99 24

E MAIL : feedback@premierin.com WEBSITE: www.premierin.com